LED-PET-SW





The Petite LED series provides high performance in a small form factor, with lumen outputs ranging from 367lm/ft to over 2290lm/ft. Available in color temperatures 2200K, 2700K, 3000K and 4000K, while maintaining 95+ CRI.

The Petite LED line is our smallest form factor LED boasting a board with of only 5mm (.19"). Pairing perfectly with our Mini and standard channel options this product is truly the apex of performance and size.

SPECIFICATIONS

CCT Output Chart									
CCT	1.5W	3.0W	4.4W	6.0W	7.0W				
2200К	112lm/ft	224lm/ft	329lm/ft	450lm/ft	523lm/ft				
2700K	119lm/ft	238lm/ft	373lm/ft	510lm/ft	593lm/ft				
3000К	126lm/ft	253lm/ft	373lm/ft	510lm/ft	593lm/ft				
4000к	149lm/ft	298lm/ft	438lm/ft	600lm/ft	697lm/ft				

Input Volt.	24V
PCB Width	5MM
CRI	>95
Cut Increment	1.97"
BIN	Single Bin
Dimming	0-10V/TRIAC
L70	50000+ Hrs
IP Rating	IP20/IP65
Operating Temp	-13-113°F

Ordering Code:

Series	Wattage		ССТ		IP Rating			Wire-In		Wire-Out	
LED-PET-SW	1.5	416 lm/ft	22k	2200K	DRY	IP20	N/A	NO LEAD	N/A	NO LEAD	
	3.0	410 III/It 833 Im/ft	22k 27k	2200K	WET	IP65	LEAD24	24" LEAD	LEAD24	24" LEAD	
	4.4	1224 Im/ft	30k	3000K			LEAD72	72" LEAD	LEAD72	72" LEAD	
	6.0	1674 lm/ft	40k	4000k			CON24	24" W/CONNECTOR	CON24	24" W/CONNECTO	
	7.0	1946 lm/ft					CON48	48" W/CONNECTOR	CON48	48" W/CONNECTOR	
							CON72	72" W/CONNECTOR	CON72	72" W/CONNECTOR	
	*Based on	3000K/DRY									






QTY:


LED-PET-SW




COMPATIBLE EXTRUSIONS



IP20 LED Strip




IP67 LED Strip



LED-PET-SW

CONNECTOR/WIRE - IN/OUT





Dynamic Driver

ACCESSORIES

Power Snap Connector



Wire to LED Strip



LED Strip to Strip Connector Mounting Strap



LED Mounting Strap (Without Channel)